

## T18R1-10K2



**Article Number:** 111-01761

**Standard Cable Tie, 4" Long, 18lb Tensile Strength, PA66, Brown/White Striped, 50/pkg**



Download spec sheet

### Base Data

<b>Local Order Number</b>	T18R1-10K2
<b>Type</b>	T18R
<b>Color</b>	White (WH) Brown (BN)
<b>Features and Benefits</b>	<ul style="list-style-type: none"> <li>• Inside serrations allow for strong hold on cables and wire bundles.</li> <li>• Head design provides high tensile strength with very low insertion force.</li> <li>• Bent tail ensures a quick and simple installation.</li> </ul>
<b>Product Description</b>	HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
<b>Short Description</b>	Standard Cable Tie, 4" Long, 18lb Tensile Strength, PA66, Brown/White Striped, 50/pkg

### Product Dimensions

<b>Minimum Tensile Strength (Imperial)</b>	18.0 lbs
<b>Minimum Tensile Strength (Metric)</b>	80.0 N
<b>Length L (Imperial)</b>	4.0 "
<b>Length L (Metric)</b>	100.0 mm
<b>Fixation Method</b>	None
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.1 "
<b>Width W (Metric)</b>	2.45 mm
<b>Bundle Diameter Min. (Imperial)</b>	0.06 "
<b>Bundle Diameter Min. (Metric)</b>	1.5 mm
<b>Bundle Diameter Max. (Imperial)</b>	0.86 "
<b>Bundle Diameter Max. (Metric)</b>	22.0 mm

### Logistics and Packaging

<b>Quantity Per</b>	bag
<b>Package Quantity (Metric)</b>	50
<b>Carton Quantity</b>	10000

### Material and Specifications

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL94 V2
<b>Halogenfree</b>	Yes
<b>Operating Temperature</b>	-40°F to +185°F (-40°C to +85°C)
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	UL-ZODZ2.E64139 MIL 53421
<b>UL Listed (US and Canada)</b>	No
<b>UL Recognized (US and Canada)</b>	No