



NOTE:
 MATERIAL AND FINISH:
 *HOUSING: PPS (UL 94V-0).
 *CONTACT: PHOSPHOR BRONZE GOLD
 PERFORMANCE SPECIFICATION:
 *CURRENT: 1 AMPERE MAX.
 *OPERATING TEMPERATURE:-55 °C TO +105°C.
 *INSULATION RESISTANCE:1000 MEGOHMS MIN.
 *DURABILITY : 40 CYCLES MIN.
 *METAL LATCH: PHOSPHOR BRONZE WITH GOLD PLATED.

LOT SIZE: NO:	A±0.2	B±0.2	C±0.2	D±0.2	E±0.2	F±0.2
SMT-28P	18.09	18.09	7.62	7.62	12.90	12.90
SMT-32P	18.04	20.60	7.62	10.16	15.40	12.90
SMT-44P	23.10	23.10	12.70	12.70	18.00	18.00
SMT-52P	25.70	25.70	15.24	15.24	20.50	20.50
SMT-68P	30.80	30.80	20.32	20.32	25.75	25.75
SMT-84P	35.95	35.95	25.40	25.40	30.90	30.90

14/09/2	Jody	EG-N1413001	Change rubber core body		A1
13/08/13	JF		NEW DWG		A0
DATE	DR.BY	ECN.NO.	DESCRIPTION	MARK	VER.
-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差參考表			CnC Tech LLC TITLE: PLCC 0.25 DIP180度 32PIN 成品		
X.X ±0.30	X.X° ±3.0°	APPD:			
X.XX ±0.15	X.XX° ±1.0°	CHECK:	DATE	SCALE	UNIT
X.XXX ±0.10	X.XXX° ±0.5°	DRAW:	2014.09.02	1:1	mm
			CD	TYPE	PAGE
			1 / 1		