



PRIMARY LEADS ARE #20 TEW
 SECONDARY LEADS ARE #16 TEW
 ALL LEADS OUT 8"-9" AND STRIPPED 0.5" MIN.
 WEIGHT: 3.75Lbs +/- 4%

HAMMOND MANUFACTURING
1182N18
 50/60Hz VA:160
 PRI: 2x 117V BLK-WHT, BRN-ORN
 SEC: 2x 18V @ 4.44A RED-BLU, GRY-YEL
 1A0160A000C018018
 MADE IN CANADA DATE PB
 RoHS Compliant
 CE, UL, and other certification marks.

SUPPLIED WITH: TWO 0.062" T X 3.75" OD RUBBER WASHERS.
 ONE 16GA X 3.56" OD STEEL MOUNTING WASHER.
 ONE 1/4-20 BOLT 2.50" LONG WITH A LOCK WASHER AND 1/4-20 HEX NUT.

ELECTRICAL DATA:		
TESTS	CONDITIONS	ACCEPTANCE CRITERIA
Sec. N.L.V	@ 117V, 60Hz BLK & BRN to WHT & ORN	
OR	@ 234V, 50Hz BLK to ORN (Connect BRN & WHT)	
	RED - BLU	19.39 V ±2%
	GRY - YEL	19.39 V ±2%
POLARITY	BLK, BRN, RED and GRY.	ADDITIVE
DCR	BLK - WHT	5.100 Ohms ±20%
IN OHMS	BRN - ORN	5.100 Ohms ±20%
	RED - BLU	0.140 Ohms ±20%
	GRY - YEL	0.140 Ohms ±20%
HI POT	PRIMARY - SECONDARY	4000V, 60Hz, 1 SEC
	PRIMARY - PRIMARY	600V, 60Hz, 1 SEC
	SECONDARY - SECONDARY	600V, 60Hz, 1 SEC

PROPERTY AND COPYRIGHT NOTICE
 THIS DRAWING AND THE INFORMATION IT CONVEYS ARE THE PROPERTY OF HAMMOND MANUFACTURING. IT MAY NOT BE REPRODUCED, TRANSMITTED OR USED IN ANY MANNER WHATSOEVER WITHOUT THE WRITTEN PERMISSION OF HAMMOND MANUFACTURING.

REV	NOTES	BY	DATE	ELECTRONIC DIVISION 52 RANKIN PLACE, WATERLOO, ONTARIO, N2J 3Z5 PHONE: 519.886.6181 FAX: 519.886.9540
TOROID POWER TRANSFORMER				DRAWN: G. GRAY DATE: 21/03/2014 APPROVED: _____ DATE: _____
NUMBER: 1182N18				