

**KEMET Part Number: M3253508E1Z184JZMB-T&R**  
(C2220K184J3EML7189)

SMD MIL C0G PRF32535, Ceramic, Military/High Reliability, 0.18 uF, 5%, 25 VDC, C0G, SMD, Low ESR, MIL-PRF-32535, N/A, 2220



General Information	
Supplier:	KEMET
Series:	SMD MIL C0G PRF32535
Style:	SMD Chip
Description:	SMD, Low ESR, MIL-PRF-32535
RoHS:	No
Termination:	Solder Plated
Failure Rate:	N/A
Qualifications:	MIL-PRF-32535 M-Level
Chip Size:	2220

Dimensions	
L	5.69mm +/-0.41mm (0.224 in +/-0.016 in)
W	5mm +/-0.41mm (0.197 in +/-0.016 in)
T	2.79mm MAX (0.11 in MAX)
B	0.64mm +/-0.46mm (0.025 in +/-0.018 in)

Specifications	
Capacitance:	0.18 uF
Capacitance Tolerance:	5%
Voltage DC:	25 VDC
Dielectric Withstanding Voltage:	62.5 V
Temperature Range:	-55/+125C
Temperature Coefficient:	C0G
Dissipation Factor:	0.25% 1MHz 25C
Aging Rate:	0% Loss/Decade Hour
Insulation Resistance:	5.56 GOhms

Packaging Specifications	
Packaging:	T&R
Packaging Quantity:	1000