



Electronics & Cable

44 Richboynton Road, Dover, NJ 07801

973 328 3200 F. 973 328 3130

#2754 - #2764 Plastic Speaker Cable - Clear And Colored Insulation

Plastic Speaker Cable

Clear And Colored Insulation

Description: Conductors are parallel, stranded copper, color coded and clear polyvinylchloride insulation. Polarity is determined by TC/BC or by identification on one leg. Conductors separate quickly when split apart. Suitable for HI-FI speaker cable, miniature juke-box speaker connections, rear audio speaker extension cable. Clear insulation blends with any interior.

Temperature Rating: -20°C To + 60°C.

Operating Voltage: 300V.

DABURN Cat. No.	No. Of Cond.	Cond. Size	Cond. Strand	Nom. Wall		Nom. OD		Stock Colors	Standard Packaging
				IN.	MM.	IN.	MM.		
2754	2	24	7/32	0.016	0.41	.057 x .120	1.45 x 3.05	BN/BK/WH/GR/TN	100', 500', 1000'
2755	2*	24	7/32	0.016	0.41	.057 x .120	1.45 x 3.05	Clear	100', 500', 1000'
2753	2	22	7/30	0.020	0.51	.070 x .140	1.78 x 3.56	Clear	100', 500', 1000'
2756	2	20	10/30	0.016	0.41	.085 x .175	2.16x 4.45	BN/BK/WH/GY/TN	100', 500', 1000'
2757	2*	20	10/30	0.016	0.41	.085 x .175	2.16x4.45	Clear	100', 500', 1000'
2758	2	18	41/34	0.032	0.81	.115 x .215	2.92 x 5.46	BN/BK/WH/GY/TN	100', 500', 1000'

2759	2	18	41/34	0.032	0.81	.115 x .215	2.92 x 5.46	Clear	100', 500', 1000'	
2760	2*	16	26/30	0.030	0.76	.115 x .215	2.92 x 5.46	Clear	100', 500', 1000'	
2761	2*	14	41/30	0.030	0.76	.140 x .290	3.56 x 7.37	Clear	100', 500', 1000'	
2765	2**	14	168/36	0.055	1.40	.200 x .415	5.08 x 10.54	Clear	100', 500', 1000'	
2766	2**	16	105/36	0.055	1.40	.160 x .355	4.06x8.51	Clear	100', 500', 1000'	
2762	2**	12	259/36	0.055	1.40	.200 x .415	5.08 x 10.54	Clear	100', 500', 1000'	
2763	2**	10	413/36	0.055	1.40	.240 x .485	6.10 x 12.32	Clear	100', 500', 1000'	
2764	2**	8	665/36	0.055	1.40	.250 x .500	6.35 x 12.70	Clear	100', 500', 1000'	

* 1 conductor tinned copper, 1 conductor bare copper.

** Extra flexible stranding.

Put-Ups: 100', 500', 1000'.

Additional Put-Ups and colors available.