

SWS100 SPECIFICATIONS


CA731-01-01B

ITEMS		MODEL	SWS100-3	SWS100-5	SWS100-12	SWS100-15	SWS100-24
1	Nominal Output Voltage	V	3.3	5	12	15	24
2	Maximum Output Current	A	20	20	8.5	6.7	4.3
3	Maximum Output Power	W	66	100	102	100.5	103.2
4	Efficiency (Typ) 115/230VAC (* 1)	%	69 / 70	75 / 77	79 / 81	81 / 83	82 / 84
5	Input Voltage Range (* 2)	-	85 ~ 265VAC (47-63Hz) or 120 ~ 370VDC				
6	Input Current (Typ) 115/230VAC (* 1)	A	0.9 / 0.5	1.2 / 0.6			
7	Inrush Current (Typ) (* 3)	-	16A at 115VAC, 32A at 230VAC, Ta=25oC, Cold Start				
8	PFHC	-	Built to meet EN61000-3-2				
9	Power Factor (Typ) 115/230VAC (* 1)	-	0.99 / 0.95				
10	Output Voltage Range	V	2.97~3.63	4.5~5.5	10.8~13.2	13.5~16.5	21.6~26.4
11	Ripple and Noise (115/230VAC) (* 1, 4)	mV	100	100	100	100	150
12	Line Regulation (* 4, 5)	mV	20	20	48	60	96
13	Load Regulation (* 4, 6)	mV	40	40	96	120	144
14	Temperature Coefficient	-	Less than 0.02%/°C				
15	Over Current Protection (* 7)	A	21~	21~	8.9~	7.0~	4.5~
16	Over Voltage Protection (* 8)	V	3.79~4.95	5.75~6.95	13.8~16.2	17.2~20.3	27.6~32.4
17	Hold-Up Time (Typ) 115/230VAC (* 1)	-	20ms				
18	Leakage current (* 9)	-	0.75mA Max, 0.25mA(Typ) at 115VAC / 0.5mA(Typ) at 230VAC				
19	Series Operation	-	Possible				
20	Operating Temperature (* 10)	-	- 10 ~ + 60 °C (Refer to Output Derating Curve)				
21	Operating Humidity	-	30 ~ 90 %RH (No dewdrop)				
22	Storage Temperature	-	- 30 ~ +85°C				
23	Storage Humidity	-	10 ~ 95%RH (No dewdrop)				
24	Cooling	-	Convection cooling				
25	Withstand Voltage	-	Input - Output : 3.0kVAC (20mA), Input - FG : 2.0kVAC (20mA) Output - FG : 500VAC (100mA) for 1min.				
26	Isolation Resistance	-	More than 100MΩ at Ta=25°C and 70%RH, Output - FG : 500VDC				
27	Vibration	-	At no operating, 10 - 55Hz (sweep for 1min) 19.6m/s ² Constant, X, Y, Z 1hour each				
28	Safety	-	Approved by UL60950-1, CSA60950-1, EN60950-1, EN50178				
29	EMI (* 1)	-	Built to meet FCC-Class B, EN55011/EN55022-B				
30	Immunity (* 1)	-	Built to meet EN61000-4-2,-3,-4,-5,-6,-8,-11				
31	Weight (Typ)	g	600				
32	Dimension	mm	45 x 96 x 188 (Refer to Outline Drawing)				

* Read instruction manual carefully , before using the power supply unit.

= NOTES=

- * 1 : At maximum output power, nominal input voltage, Ta = 25°C.
- * 2 : For cases where conformance to various safety specs (UL, CSA, EN) are required, to be described as 100 - 240VAC, 50 / 60Hz on name plate.
- * 3 : Not applicable for the in-rush current to Noise Filter for less than 0.2ms.
- * 4 : Please refer to Fig A for measurement of line & load regulation, ripple and noise voltage.
Ripple & noise are measured at 20MHz by using a 12" twisted pair terminated with a 0.1uF and 47uF capacitor.
- * 5 : 85 - 265VAC, constant load.
- * 6 : No load - Full load(Maximum power), constant input voltage.
- * 7 : Constant current limit with automatic recovery.
Avoid to operate at overload or dead short for more than 30seconds.
- * 8 : OVP circuit will shutdown output, manual reset (Re power on).
- * 9 : Measured by each measuring method of UL, CSA, EN.
- * 10: Refer to Output Derating Curve (next page) for details of output derating versus ambient temperature and mounting method .




Measurement point for Vo Line/Load Regulation, and ripple and noise.

SWS100 OUTPUT DERATING

CA731-01-02A

SWS100-3,5,12,15,24 OUTPUT DERATING VS Ta CURVE (CONVECTION COOLING)



Force Air Cooling :

Recommended minimum air velocity is 1.2m/s, flow through the component side of power suppl

SWS100-3,5,12,15,24 OUTPUT DERATING VS Ta CURVE (FORCE AIR COOLING)

