



RECOMMENDED P.C. BOARD HOLE LAYOUT

- 1 "AMP", "CSA", "▼", AND "DATE CODE" WITH .062 ± 0.015 HIGH CHARACTERS WHERE SIZE PERMITS.
- 2 HOUSING: 1-70 POSITION SIZES MAY BE PPS, GLASS-FILLED OR PCT, GLASS-FILLED. POSITION SIZES GREATER THAN 70 WILL BE PPS, GLASS-FILLED.
- 3 CONTACT: PHOSPHOR BRONZE.
- 4 CONTACT FINISH: DUPLEX PLATED 0.00076 [.000030] GOLD IN CONTACT AREA, 0.00127-0.00254 [.000050-.000100] BRIGHT TIN-LEAD ON SOLDER TAILS, ALL OVER 0.00127 [.000050] NICKEL.
- 5 THESE DIMENSIONS PERTAIN TO CAVITY Q'S ONLY, NOT TO CONTACT LOCATIONS.
- 6 POINT OF MEASUREMENT FOR PLATING THICKNESS (INSIDE CONTACT BEAMS).
- 7 CSA LOGO INK STAMPED WHITE ON HOUSING.
- 8 CONTACT FINISH: DUPLEX PLATED 0.00076 [.000030] GOLD IN CONTACT AREA, 0.00127-0.00254 [.000050-.000100] MATTE TIN ON SOLDER TAILS, ALL OVER 0.00127 [.000050] NICKEL.
- 9 ROHS 2002/95/EC COMPLIANT.
- 10 RECESSED AREA AROUND MOLD GATE IS OPTIONAL. THIS FEATURE IS ALLOWABLE ON EITHER SIDE OF HOUSING OR MAY NOT BE PRESENT AT ALL.
- 11 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

FINISH	B	A	NO OF POSN	PART NUMBER	FINISH	B	A	NO OF POSN	PART NUMBER					
11	OBSOLETE			235.15 [9.258]	89	180	7-533009-8	9	OBSOLETE	235.15 [9.258]	89	180	2-533009-8	
11	OBSOLETE			62.43 [2.458]	21	44	7-533009-7	9	OBSOLETE	62.43 [2.458]	21	44	2-533009-7	
11	OBSOLETE			209.75 [8.258]	79	160	7-533009-6	9	OBSOLETE	209.75 [8.258]	79	160	2-533009-6	
11	OBSOLETE			125.93 [4.958]	46	94	7-533009-5	9	OBSOLETE	125.93 [4.958]	46	94	2-533009-5	
11	OBSOLETE			24.33 [.958]	6	14	7-533009-4	9	OBSOLETE	24.33 [.958]	6	14	2-533009-4	
11	OBSOLETE			260.55 [10.258]	99	200	7-533009-3	9	OBSOLETE	260.55 [10.258]	99	200	2-533009-3	
11	OBSOLETE			194.51 [7.658]	73	148	7-533009-2	9	OBSOLETE	194.51 [7.658]	73	148	2-533009-2	
11	OBSOLETE			184.35 [7.258]	69	140	7-533009-1	9	OBSOLETE	184.35 [7.258]	69	140	2-533009-1	
11	OBSOLETE			171.65 [6.758]	64	130	7-533009-0	9	OBSOLETE	171.65 [6.758]	64	130	2-533009-0	
11	OBSOLETE			169.11 [6.658]	63	128	6-533009-9	9	OBSOLETE	169.11 [6.658]	63	128	1-533009-9	
11	OBSOLETE			158.95 [6.258]	59	120	6-533009-8	9	OBSOLETE	158.95 [6.258]	59	120	1-533009-8	
11	OBSOLETE			146.25 [5.758]	54	110	6-533009-7	9	OBSOLETE	146.25 [5.758]	54	110	1-533009-7	
11	OBSOLETE			133.55 [5.258]	49	100	6-533009-6	9	11	OBSOLETE	133.55 [5.258]	49	100	1-533009-6
11	OBSOLETE			128.47 [5.058]	47	96	6-533009-5	9	11	OBSOLETE	128.47 [5.058]	47	96	1-533009-5
11	OBSOLETE	8		120.85 [4.758]	44	90	6-533009-4	9	OBSOLETE	120.85 [4.758]	44	90	1-533009-4	
11	OBSOLETE			113.23 [4.558]	42	86	6-533009-3	9	11	OBSOLETE	113.23 [4.558]	42	86	1-533009-3
11	OBSOLETE			108.15 [4.258]	39	80	6-533009-2	9	11	OBSOLETE	108.15 [4.258]	39	80	1-533009-2
11	OBSOLETE			97.99 [3.858]	35	72	6-533009-1	9	OBSOLETE	97.99 [3.858]	35	72	1-533009-1	
11	OBSOLETE			95.45 [3.758]	34	70	6-533009-0	9	OBSOLETE	95.45 [3.758]	34	70	1-533009-0	
11	OBSOLETE			82.75 [3.258]	29	60	5-533009-9	9	11	OBSOLETE	82.75 [3.258]	29	60	533009-9
11	OBSOLETE			70.05 [2.758]	24	50	5-533009-8	9	11	OBSOLETE	70.05 [2.758]	24	50	533009-8
11	OBSOLETE			57.35 [2.258]	19	40	5-533009-7	9	OBSOLETE	57.35 [2.258]	19	40	533009-7	
11	OBSOLETE			52.27 [2.058]	17	36	5-533009-6	9	OBSOLETE	52.27 [2.058]	17	36	533009-6	
11	OBSOLETE			44.65 [1.758]	14	30	5-533009-5	9	11	OBSOLETE	44.65 [1.758]	14	30	533009-5
11	OBSOLETE			27.03 [1.458]	11	24	5-533009-4	9	OBSOLETE	27.03 [1.458]	11	24	533009-4	
11	OBSOLETE			31.95 [1.258]	9	20	5-533009-3	9	OBSOLETE	31.95 [1.258]	9	20	533009-3	
11	OBSOLETE			26.87 [1.058]	7	16	5-533009-2	9	OBSOLETE	26.87 [1.058]	7	16	533009-2	
11	OBSOLETE			21.79 [1.858]	5	12	5-533009-1	9	11	OBSOLETE	21.79 [1.858]	5	12	533009-1

THIS DRAWING IS A CONTROLLED DOCUMENT. DWN: K.L.CLOUSER/UTA 3/6/91
CHK: D.SARVER 5/14/91

STE TE Connectivity

RECEPTACLE ASSY, MOD II, DBL ROW, 2.54 X 2.54 [.100 X .100] CL, GUIDE PIN EARS, CLOSED ENTRY.

SIZE: A1 CAGE CODE: 00779 DRAWING NO: 533009 RESTRICTED TO
WEIGHT: --
CUSTOMER DRAWING SCALE: 6:1 SHEET: 1 OF 1 REV: V4