



**Mallory Sonalert Products, Inc.**

Part #: **SCE028LD3MG5B**

**Sales Outline Drawing**

Revision: **C**

**Specifications:**

|                        |  |                            |                             |                            |
|------------------------|--|----------------------------|-----------------------------|----------------------------|
| Sound Level Category:  | Loud   | Loud                       | Loud                        | Medium                     |
| Mode of Operation:     | Continuous   | Double Pulse               | Dual Tone                   | Siren Sweep                |
| Loudness @ 2 FT:       | 85 to 95 dB(A) Typ.  | 85 to 95 dB(A) Typ.        | 75 to 85 dB(A) Typ.         | 75 to 85 dB(A) Typ.        |
| Pulse Rate (PPS):      | N/A  | 2                          | 7                           | 5                          |
| Frequency:             | 2900 ± 500 Hz  | 2900 ± 500 Hz              | 3.0 - 2.9 kHz               | 2.6 - 3.2 kHz              |
| Connection:            | T-BLOCK ONLY   | T-BLOCK; BLACK WIRE TO (-) | T-BLOCK; YELLOW WIRE TO (-) | T-BLOCK; BOTH WIRES TO (-) |
| Voltage Rating:        | 16 to 28 VDC   |                            |                             |                            |
| Current Draw:          | 40mA MAX   |                            |                             |                            |
| Housing Material:      | 6/6 Nylon, Color: Black  |                            |                             |                            |
| Storage Temperature:   | -40° to +85° C   |                            |                             |                            |
| Operating Temperature: | -40° to +85° C   |                            |                             |                            |
| Panel Mounting:        | Recommended hole size is 1.25"(31.75mm). Thread front will fit standard 30mm(1.181") hole. |                            |                             |                            |
| Knurled Nut:           | Used to attach part to panel. The max recommended torque is 10 in-lbs.                     |                            |                             |                            |
| Weight (Typical):      | 1.6 oz (45g)   |                            |                             |                            |
| NEMA 3R,4X, & 12:      | Approved with use of ACC03.  |                            |                             |                            |
| cUL Recognition:       | cUL Recognized   |                            |                             |                            |
| Options:               | Please contact factory.  |                            |                             |                            |

**Dimensions:** Inches (mm)                      **cUL Recognized**                      **ROHS Compliant**

