


MSD INC.

ENGINEERING DATA SHEET

RELAY TYPE: FCB-205-0127M | COMPUTER PART No.: 934753Q | TEST PROCEDURE
 CUSTOMER/SPECIFICATION: M83536/1-027M | REV NONE | MSDP-790

TEST REQUIREMENTS

COIL RES.: $\pm 10\%$ 500 OHMS | OPERATE TIME: ms MAX | RELEASE TIME: ms MAX
 CONTACT MAKE BOUNCE: 1ms MAX | N.O. BREAK BOUNCE: N/A
 CONTACT STABILIZATION TIME: 2.5 ms MAX | RATED COIL VOLTAGE: 28Vdc
 CONTACT RES.: MFG TEST: .040 OHMS @ 10mA-6Vdc | FINAL TEST: .050 OHMS @ 10mA-6Vdc
 CONTACT VOLTAGE DROP: FINAL TEST: .100 V MAX @ 5A-6Vdc
 HI-POT: 1000 Vrms ALL POINTS
 INSULATION RESISTANCE: 100 MEGOHMS MIN. @ 500 Vdc
 VIBRATION: MIL-STD-202, METHOD 204 (30G's/100-3000Hz)
 SEAL TEST: 1×10^{-8} MAX LEAK RATE | COIL TRANSIENT SUPPRESSION: N/A
 OTHER: _____



Prepared By: Date		Approved By: Date	
LES WYNNE 3-20-96		<i>[Signature]</i> 3-21-96	
Rev	ECN No.	Date	

SPECIAL INSTRUCTIONS