



CIRCUIT: SPDT

CONTACT CONFIGURATION

SWITCH FUNCTION		
POS. 1	POS. 2	POS. 3
DN	OFF	(DN)
2-3	OPEN	2-1

( ) =Momentary

- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
  2. GENERAL TOLERANCE: 0.0=±0.4  
0.00=±0.25
  3. TERM. NOS. FOR REF. ONLY
  4. CONTACT RATING: 5A, @120VAC or 28VDC; 2A, @250VAC.
  5. ELECTRICAL LIFE: 50,000 make-and-break cycles at full load.
  6. INSULATION RESISTANCE: 1,000 M Ohms min.
  7. DIELECTRIC STRENGTH: 1,000 V RMS @sed level.
  8. OPERATING TEMP.: -30°C to 85°C

C	15971	ADD *BLK* TO TITLE	5/1/06	BK
B	14309	CORRECT FRONT VIEW	9/10/04	AR
A	10123	RELEASED FOR PRODUCTION	2/15/99	MM
REV.	ECN No.	DESCRIPTION	DATE	CHKD

TITLE		SCALE	DATE	DR	DWG	REV
300SP5J3BLKV52QE		2:1	2/15/99	MM	T315003	C

**E-SWITCH®**

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED