






<b>APPLICABLE STANDARD</b>		USB2.0 SPECIFICATION AND MICRO-USB CABLES AND CONNECTORS SPECIFICATION 		
RATING	OPERATING TEMPERATURE RANGE	-30 °C TO +85° C 	STORAGE TEMPERATURE RANGE	-30 °C TO +85 °C 
	VOLTAGE	-	OPERATING HUMIDITY RANGE	- % TO - %
	CURRENT	-	APPLICABLE CABLE	-

### SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
<b>CONSTRUCTION</b>				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X

	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	
	3	DIS-E-001673	TS. SAKAI ZAWA	KN. ICHIKAWA	07. 07. 24	
REMARK				APPROVED	AO. SUZUKI	07. 03. 06
				CHECKED	HK. TANAKA	07. 03. 06
				DESIGNED	TS. SAKAI ZAWA	07. 03. 06
				DRAWN	TS. SAKAI ZAWA	07. 03. 06
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.	ELC4-126148-00		

	SPECIFICATION SHEET	PART NO.	ZX20-B-SLDC		
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL242-0022-1-00		1/1