

MCPK, CC393, TC114 SERIES

8 SERIES IP67 FIELD TERMINATION KIT

Mates with:
MCR(K), MCP(K)

SPECIFICATIONS

For complete specifications see www.samtec.com?MCPK

- Insulator Material:** PPS
- Terminal Material:** Phosphor Bronze
- Contact Material:** Phosphor Bronze
- Operating Temp Range:** -20 °C to +80 °C
- Gasket Material:** Silicone
- Spring Material:** Stainless Steel
- Coupling Ring Spacer:** PBT
- Cable Clamp:** POM
- RoHS Compliant:** Yes

DUST CAPS


- -S (Socket) = DCA-MCR-8
 - -T (Terminal) = DCA-MCP-8
- Visit sealedio.samtec.com for a complete list of sealed systems

Note: Samtec's MCPK Series is dual sourced by Hirose Electric Co., LTD.




-T = Terminal (12 positions)

-S = Socket (12 positions)



-S GENDER



-T GENDER

SPECIFICATIONS

For complete specifications see www.samtec.com?CC393 or www.samtec.com?TC114

Plating:
10 μm (0.25 μm) Gold on contact

TOOLING

- Hand tool:
CAT-HT-393-2430-13
- Mini Applicator
(28-30 AWG):
CAT-MA-393-2830-XX-01
- Extraction Tool:
CAT-EX-MCX-8-01



CC393
= Contact


TC114
= Terminal

-2830
= 28 to 30 AWG


-S
= Strip
(15 contacts or terminals)

-M
= Mini Reel
(1,000 - 5,000 contacts or terminals)

-R
= Reel
(20,000 contacts or terminals)



-CC393



-TC114