



FEATURES

- Double Bayonet Base - Non-Polarized
- Wide Input Voltage Range
- Low Power Usage
- Omni Directional Light Distribution
- Efficacy of 95Lm/Watt
- CRI > 80

VOLTAGE AC/DC			WATTS			ILLUMINANCE FLUX lm TYP	COLOR DEGREE K
MIN	NOM	MAX	MIN	NOM	MAX		
10	12	30	2.0	2.4	2.8	230	3000

JKL PART NUMBER: LE-BA15D-12WW

<p>THIRD ANGLE PROJECTION</p>			<p>DIMENSIONS ARE IN MILLIMETERS</p> <p>TOLERANCE UNLESS OTHERWISE SPECIFIED</p> <p>1 PL +/- REF.</p> <p>2 PL +/- REF.</p> <p>ANGLE +/-</p>		<p>JKL COMPONENTS CORPORATION</p>														
			<p>DRAWN BY L. WENGSTROM</p>		<p>APP'VD BY DATE 11/6/15</p>		<p>SIZE A</p>		<p>FSCM NO. 55335</p>		<p>DRAWING NO. LE-BA15D-12WW</p>								
<p>RELEASED</p>			<p>11/6/15</p>		<p>- CAD DRAWING -</p>					<p>SCALE NONE</p>		<p>RELEASED DATE 11/6/15</p>		<p>REVISION DATE</p>		<p>REV. NO.</p>		<p>SHEET 1 OF 1</p>	
<p>REV. NO.</p>			<p>DESCRIPTION/ECO NUMBER</p>		<p>APP'VD DATE</p>		<p>MANUAL REVISIONS NOT PERMITTED</p>					<p>DATE 11/6/15</p>		<p>DATE</p>		<p>NO.</p>		<p>1 OF 1</p>	