

**RS ELCO  
RS ELCOF 56/56RM S**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 1429-0  
Fax: +49 5231 14292083  
www.weidmueller.com



ELCO contacts inserts are used in electrical power plants, refineries and a variety of process applications – wherever stable and reliable signal transmission is required. The ELCO connector features both a reliable connection system and a high signal capacity.

The line of RS ELCO interfaces and pre-assembled PAC ELCO cables is a specially designed solution for these requirements.

**General ordering data**

Type	RS ELCOF 56/56RM S
Order No.	<a href="#">1480780000</a>
Version	Interface, RS ELCO, ELCO plug-in connector, 56, LP2N 5.08mm
GTIN (EAN)	4050118289640
Qty.	1 pc(s).

**RS ELCO**  
**RS ELCOF 56/56RM S**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 1429-0  
 Fax: +49 5231 14292083  
 www.weidmueller.com

**Technical data****Dimensions and weights**

Length	155 mm	Length (inches)	6.102 inch
Width	70 mm	Width (inches)	2.756 inch
Height	60 mm	Height (inches)	2.362 inch
Net weight	175 g		

**Temperatures**

Operating temperature	-25...50 °C	Storage temperature	-40...60 °C
-----------------------	-------------	---------------------	-------------

**Connection Data**

Connection on control side	ELCO plug-in connector	Number of poles (control side)	56-pole female
Contact material (control side)	Phosphor bronze alloy	Polarity hardware codification	1
Connection (field side)	LP2N 5.08mm	Number of poles (field side)	56 P
Earthing	No		

**Rating data**

Rated voltage	150 V AC / 200 V DC	Rated current per connection	5 A
Total operating current	280 A		

**Insulation coordination (EN50178)**

According to	DIN EN 50178	Rated insulation voltage	< 150 V AC
Surge voltage category	II	Pollution severity level	2
Pulse voltage test (1,2/50µs)	2.5 kV	Insulation test voltage	0.8 kVAC

**Connection field**

Type of connection	Clamping yoke connection	Clamping range, min.	0.13 mm <sup>2</sup>
Clamping range, max.	6 mm <sup>2</sup>	Solid, min. H05(07) V-U	0.5 mm <sup>2</sup>
Solid, max. H05(07) V-U	6 mm <sup>2</sup>	Flexible, min. H05(07) V-K	0.5 mm <sup>2</sup>
Flexible, max. H05(07) V-K	4 mm <sup>2</sup>	Flexible with sleeve, max.	2.5 mm <sup>2</sup>
Flexible with sleeve, min.	0.5 mm <sup>2</sup>	Sleeve with plastic collar, max.	2.5 mm <sup>2</sup>
Min. wire cross-section, AWG	AWG 12	Max. wire cross-section, AWG	AWG 26
Tightening torque, min.	0.5 Nm	Tightening torque, max.	0.6 Nm
Stripping length	6 mm		

**Classifications**

ETIM 4.0	EC000237	ETIM 6.0	EC002780
eClass 6.2	27-14-11-52	eClass 9.1	27-14-11-52

**Product information**

Descriptive text technical data	Polariser in position 1
Descriptive text accessories	Refer to the "PAC-ELCO universal cables" section in this chapter

**Approvals**

Approvals



Creation date October 30, 2017 9:31:23 PM CET

Catalogue status 20.10.2017 / We reserve the right to make technical changes.

2

**Data sheet**

**RS ELCO**  
**RS ELCOF 56/56RM S**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 1429-0  
Fax: +49 5231 14292083  
www.weidmueller.com

**Technical data**

**Downloads**

User Documentation

[Table of connections](#)

**Data sheet**

**RS ELCO  
RS ELCOF 56/56RM S**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 1429-0  
Fax: +49 5231 14292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

