

Part Number: 5341UE

Security & Sound, #18-2pr, BC, CMR



Product Description

Security & Sound Cable, Riser-CMR, 2-18 AWG stranded bare copper pairs with polyolefin insulation, PVC jacket with ripcord

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Pairs
18	7x26	BC - Bare Copper	2

Conductor Count:	4
Conductor Size:	18 AWG

Insulation

Material	Nominal Wall Thickness
PP - Polypropylene	0.007 in

Color Chart

Number	Color
1	Black & Red
2	Black & White

Outer Shield Material

Material
Unshielded

Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness	Ripcord
PVC - Polyvinyl Chloride	0.246 in	0.017 in	Yes

Construction and Dimensions

Print Legend:	NEW GENERATION(R) BY BELDEN-M 5341UE CMR 75C 2PR18 (UL) E108998 OR C(UL) CMG (2 FT., 7 DIGIT SEQUENTIAL) FEET
---------------	---

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR
6.55 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor
29 pF/ft

Shielding:	Unshielded
------------	------------

Current

Max. Recommended Current [A]
4 Amps per conductor @ 20°C A

Voltage

UL Voltage Rating

300 V RMS

Temperature Range

Operating Temp Range:	-20°C To +75°C
-----------------------	----------------

Mechanical Characteristics

Bulk Cable Weight:	32.8 lbs/1000ft
Max Recommended Pulling Tension:	90 lbs
Min Bend Radius/Minor Axis:	2.5 in

Standards

NEC/(UL) Specification:	CMR
CEC/C(UL) Specification:	CMG
CPR Euroclass:	Eca

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flammability, LSOH, Toxicity Testing

CSA Flammability:	FT4
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	6341UE

Part Number

Variants

Item #	Color	Footnote
5341UE.00305	Chrome	
5341UE 0081000	Gray	C
5341UE 008U1000	Gray	

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.