

## Thermomagnetic device circuit breaker - TMC 2 F1 120 0,2A - 0914730

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Thermomagnetic circuit breaker, 2-pos., fast blow, 1 N/O contact and 1 N/C contact, with universal foot for mounting on NS 32 or NS 35

The illustration shows version TMC 1  
F1 100 1A



### Key Commercial Data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 STK    |
| Weight per Piece (excluding packing) | 138.6 g  |
| Custom tariff number                 | 85362010 |
| Country of origin                    | Germany  |

### Technical data

#### General

|  |                 |
|--|-----------------|
| Number of levels                       | 2               |
| Number of connections                  | 4               |
| Mounting type                          | DIN rail: 35 mm |
| Color                                  | black           |
| Number of positions                    | 2               |
| Overvoltage category                   | II              |
| Insulating material                    | PA66            |
| Flammability rating according to UL 94 | V-2             |

#### Electrical data

|                     |                       |
|---------------------|-----------------------|
| Fuse type           | Automatic device      |
| Rated surge voltage | 2.5 kV                |
| Rated voltage       | 250 V AC (3 AC 433 V) |

# Thermomagnetic device circuit breaker - TMC 2 F1 120 0,2A - 0914730

## Technical data

### Electrical data

|   |                                       |
|---|---------------------------------------|
|   | 65 V DC                               |
| Rated current $I_N$                             | 0.2 A                                 |
| Insulation resistance $R_{iso}$                 | > 100 M $\Omega$ (500 V DC)           |
| Rated short-circuit switching capacity $I_{cn}$ | 400 A                                 |
|   | 2500 A (32 V DC)                      |
| Short-circuit switching capacity $I_k$          | 5000 A                                |
|   | 2000 A UL 1077: 65 V DC               |
| Dielectric strength                             | 3000 V AC (Actuation area)            |
|   | 3000 V AC (Main to auxiliary circuit) |
|   | 1500 V AC (Position to position)      |
| Switching cycles, max.                          | 10000 (At 1 x $I_n$ , inductive)      |
| Degree of pollution                             | 2                                     |
| Overvoltage category                            | II                                    |
| Insulating material group                       | II                                    |

### Dimensions

|        |         |
|--------|---------|
| Height | 82.5 mm |
| Width  | 25 mm   |
| Depth  | 96 mm   |

### Ambient conditions

|                                 |                        |
|---------------------------------|------------------------|
| Degree of protection            | IP30 (Actuation area)  |
|                                 | IP20 (Connection area) |
| Ambient temperature (operation) | -30 °C ... 60 °C       |

### Connection data

|  |                      |
|--|----------------------|
| Conductor cross section solid min.   | 0.2 mm <sup>2</sup>  |
| Conductor cross section solid max.   | 6 mm <sup>2</sup>    |
| Conductor cross section flexible min.                                      | 0.2 mm <sup>2</sup>  |
| Conductor cross section flexible max.                                      | 4 mm <sup>2</sup>    |
| Conductor cross section AWG min.   | 24                   |
| Conductor cross section AWG max.   | 10                   |
| Conductor cross section flexible, with ferrule without plastic sleeve min. | 0.25 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule without plastic sleeve max. | 4 mm <sup>2</sup>    |
| Conductor cross section flexible, with ferrule with plastic sleeve min.    | 0.25 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule with plastic sleeve max.    | 2.5 mm <sup>2</sup>  |
| 2 conductors with same cross section, solid min.                           | 0.2 mm <sup>2</sup>  |
| 2 conductors with same cross section, solid max.                           | 0.75 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded min.                        | 0.2 mm <sup>2</sup>  |

# Thermomagnetic device circuit breaker - TMC 2 F1 120 0,2A - 0914730

## Technical data

### Connection data

|   |                      |
|---|----------------------|
| 2 conductors with same cross section, stranded max.                                     | 0.75 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, min.   | 0.25 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, max.   | 1 mm <sup>2</sup>    |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. | 0.5 mm <sup>2</sup>  |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. | 2.5 mm <sup>2</sup>  |
| Connection method   | Screw connection     |
| Stripping length  | 12 mm                |
| Internal cylindrical gage   | A3                   |
| Screw thread  | M3                   |
| Tightening torque, min  | 0.6 Nm               |
| Tightening torque max   | 0.8 Nm               |

### Standards and Regulations

|                          |          |
|--------------------------|----------|
| Standards/specifications | EN 60934 |
|                          | UL 1077  |

## Drawings

### Diagram

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27141116 |
| eCl@ss 4.1 | 27141116 |
| eCl@ss 5.0 | 27141116 |
| eCl@ss 5.1 | 27141116 |
| eCl@ss 6.0 | 27141116 |
| eCl@ss 7.0 | 27141116 |
| eCl@ss 8.0 | 27141116 |
| eCl@ss 9.0 | 27141116 |

### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000899 |
| ETIM 3.0 | EC000899 |

# Thermomagnetic device circuit breaker - TMC 2 F1 120 0,2A - 0914730

## Classifications

### ETIM

|          |          |
|----------|----------|
| ETIM 4.0 | EC000899 |
| ETIM 5.0 | EC000899 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211812 |
| UNSPSC 7.0901 | 39121411 |
| UNSPSC 11     | 39121411 |
| UNSPSC 12.01  | 39121411 |
| UNSPSC 13.2   | 39121411 |

## Approvals

### Approvals

---

#### Approvals

CSA / UL Recognized / VDE Zeichengenehmigung / EAC

---





#### Ex Approvals

---

#### Approvals submitted

---

## Approval details



## Thermomagnetic device circuit breaker - TMC 2 F1 120 0,2A - 0914730

### Accessories

#### Accessories

#### DIN rail

DIN rail, unperforated - NS 35/ 7,5 CU UNPERF 2000MM - 0801762



DIN rail, material: Copper, unperforated, height 7.5 mm, width 35 mm, length: 2 m

---

DIN rail, unperforated - NS 32 CU/120QMM UNPERF 2000MM - 1201280



G-profile DIN rail, deep-drawn, material: Copper, unperforated, height 15 mm, width 32 mm, length 2 m

---

DIN rail, unperforated - NS 35/15 UNPERF 2000MM - 1201714



DIN rail, material: Steel, unperforated, height 15 mm, width 35 mm, length: 2 m

---

DIN rail, unperforated - NS 32 CU/35QMM UNPERF 2000MM - 1201358



G-profile DIN rail, material: Copper, unperforated, height 15 mm, width 32 mm, length 2 m

---

DIN rail, unperforated - NS 32 AL UNPERF 2000MM - 1201028



G rail 32 mm (NS 32)

## Thermomagnetic device circuit breaker - TMC 2 F1 120 0,2A - 0914730

### Accessories

---

DIN rail, unperforated - NS 32 UNPERF 2000MM - 1201015



G-profile DIN rail, material: Steel, unperforated, height 15 mm, width 32 mm, length 2 m

---

DIN rail perforated - NS 32 PERF 2000MM - 1201002



G-profile DIN rail, material: Steel, perforated, height 15 mm, width 32 mm, length 2 m

---

DIN rail, unperforated - NS 35/15 CU UNPERF 2000MM - 1201895



DIN rail, material: Copper, unperforated, 1.5 mm thick, height 15 mm, width 35 mm, length: 2 m

---

DIN rail, unperforated - NS 35/15-2,3 UNPERF 2000MM - 1201798



DIN rail, material: Steel, unperforated, 2.3 mm thick, height 15 mm, width 35 mm, length: 2 m

---

DIN rail, unperforated - NS 35/15 AL UNPERF 2000MM - 1201756



DIN rail, deep drawn, high profile, unperforated, 1.5 mm thick, material: aluminum, height 15 mm, width 35 mm, length 2000 mm

---

## Thermomagnetic device circuit breaker - TMC 2 F1 120 0,2A - 0914730

### Accessories

DIN rail perforated - NS 35/15 PERF 2000MM - 1201730



DIN rail, material: steel galvanized and passivated with a thick layer, perforated, height 15 mm, width 35 mm, length: 2000 mm

---

DIN rail perforated - NS 35/ 7,5 PERF 2000MM - 0801733



DIN rail, material: steel galvanized and passivated with a thick layer, perforated, height 7.5 mm, width 35 mm, length: 2000 mm

---

### End block

End clamp - E/UK 1 - 1201413



End clamps, for supporting the ends of double-level and three-level terminal blocks, width: 10 mm, color: gray

---

### Insertion bridge

Insertion bridge - EB 80-12 - 3009338



Insertion bridge, Pitch: 12 mm, Number of positions: 80, Color: gray

---

### Screwdriver tools

## Thermomagnetic device circuit breaker - TMC 2 F1 120 0,2A - 0914730

### Accessories

Screwdriver - SZS 0,6X3,5 - 1205053



Actuation tool, for ST terminal blocks, insulated, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip