

SAC-4P- 2,0-28X/M12FS SH OD


Order No.: 1454150



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1454150>

Sensor/Actuator cable, 4-position, PE-X halogen-free, Black-gray RAL 7021, shielded, Free conductor end, on Socket, straight M12, A - standard, Cable length: 2 m

Commercial data

| | |
|--------------------------|--|
| GTIN (EAN) |  4 046356 568760 |
| Note | Made-to-order |
| sales group | D117 |
| Pack | 1 pcs. |
| Customs tariff | 85444290 |
| Catalog page information | Page 220 (PC-2011) |

Product notes

WEEE/RoHS-compliant since:
03/04/2010



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General data

| | |
|-----------------------|--------|
| Rated current at 40°C | 4 A |
| Rated voltage | 250 V |
| Number of positions | 4 |
| Volume resistance | ≤ 5 mΩ |

| | |
|---------------------------------|---|
| Insulation resistance | ≥ 100 MΩ |
| Length of cable | 2 m |
| Ambient temperature (operation) | -40 °C ... 105 °C |
| | -40 °C ... 85 °C (On sudden changes in temperature (according to IEC 60512-11-4)) |

General characteristics

| | |
|-----------------------------|-------------------------------|
| Standards/regulations | M12 connector IEC 61076-2-101 |
| Coding | A - standard |
| Pollution degree | 3 |
| Degree of protection | IP65/IP68/IP69K |
| Insertion/withdrawal cycles | ≥ 100 |
| Torque | 0.4 Nm (M12 connector) |
| Contact material | CuSn |
| Contact surface material | Ni/Au |
| Contact carrier material | PP |
| Material of grip body | PP |
| Material, knurls | High-grade steel |
| Sealing material | FPM |
| Status display | No |

Conductor data

| | |
|------------------------------------|-------------------------------------|
| Cable type | PE-X black |
| Cable type (abbreviation) | 28X |
| Cable abbreviation | Li2X2X-C-VI-2X |
| Conductor cross section | 0.5 mm ² |
| AWG signal line | 20 |
| Conductor structure signal line | 28x 0.15 mm |
| Core diameter including insulation | 1.6 mm ±0.05 mm |
| Thickness, insulation | ~ 0.3 mm (Core insulation) |
| | Approx. 0.7 mm (Outer cable sheath) |
| | ~ 0.45 mm (Inner sheath) |
| External cable diameter | 6.8 mm ±0.2 mm |
| Wire colors | Brown, white, blue, black |
| External sheath, color | Black-gray RAL 7021 |
| Insulation resistance | ≥ 100 MΩ*km (at 20°C) |
| Conductor resistance | max. 39 Ω/m (at 20°C) |

| | |
|---|---|
| Nominal voltage, conductor | ≤ 300 V |
| Test voltage, conductor | ≥ 3000 V |
| Overall twist | 4 wires, twisted |
| Length of twist, overall twist | 108.8 mm |
| Shielding | Braided copper wires |
| Optical shield covering | 85 % |
| Outer sheath, material | PE-X |
| Material, inner sheath | PE-X |
| Material conductor insulation | PE-X |
| Conductor material | Bare Cu litz wires |
| Cable weight | 74 kg/km |
| Smallest bending radius, fixed installation | 34 mm |
| Smallest bending radius, movable installation | 68 mm |
| Number of bending cycles | 1000000 |
| Bending radius | 68 mm |
| Traversing path | 10 m |
| Traversing rate | 3 m/s |
| Acceleration | 10 m/s ² |
| Ambient temperature (operation) | -30 °C ... 105 °C (cable, fixed installation) -15 °C ... 105 °C (cable, flexible installation) |
| Flame resistance | According to DIN 60332-1-2 According to DIN EN 50266-2-5 |
| Halogen-free | in accordance with DIN VDE 0472 part 815 |
| Resistance to oil | in accordance with DIN EN 60811-2-1 |
| Other resistance | UV resistant According to DIN VDE 0276-605 |


Accessories

| Item | Designation | Description |
|----------------|------------------------------|---|
| General | | |
| 1440025 | SACC-M12MS-5CON-DM 5-8 SH VA | Sensor/actuator connector, socket, straight, 5-pos., M12 shielded, screw connection, high-grade steel knurl, cable screw connection 5 mm - 8.6 mm |
| Tools | | |
| 1212513 | SAC BIT M12-W14 | SAC nut, for assembling M12 connectors with hexagonal high-grade steel knurl, with 4 mm hexagonal drive |

| | | |
|---------|------------|--|
| 1208429 | TSD 04 SAC | Torque screwdriver, with preset torque of 0.4 Nm and 4 mm hexagonal drive for M12 connectors |
|---------|------------|--|


Diagrams/Drawings

Dimensioned drawing




M12 x 1 female connector, straight

Circuit diagram



Contact assignment of the M12 socket

Schematic diagram



Pin assignment M12 socket, 4-pos., A-coded, view female side

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;