

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	AI	REVISED PER ECO-11-005140	02APR2011	RK	HMR

Dimensions: 9.5 REF, 7.4 REF, 33 REF, 14.3, 12.1, 9.9, 7.7, 5.5, 3.3, 1.1, 0, 1.1, 3.3, 5.5, 7.7, 9.9, 12.1, 1.8, 0, 1.2

Dimension: 21 REF

Dimensions: 15.8 REF, 12±0.10, PBT
Labels: CIRCUIT NUMBER, LOGO MARK

Dimension: 1±0.2

TABLE - 1

POS 極数	CAP ASSEMBLY PART NO キャップ 型番	MOUNT TYPE 取付種類
28	1565373	H TYPE
	1565375	V TYPE
	1565377	W to W

TABLE - 2

		TERMINAL NO 端子型番	APPLICABLE WIRE RANGE 適用電線
SIGNAL 025	TIN	1123343-1	AVSS/AVSSH-f/AESSX 0.3~0.5mm ² CAVS/CAVUS 0.22~0.5mm ²

TABLE - 3

PAPER BOX ダンボール箱	PLASTIC BAG ビニール袋	NATURAL (自然色)	1565380-1
OUTER 外装	INNER 内装	HOUSING COLOR ハウジング色	P/N 型番
PACKING STYLE 梱包形態			

1. RETAINER SHOULD BE SET TO THE PRE- ASSEMBLY POSITION WITHIN THE PLUG HOUSING WHEN SHIPPED TO THE CUSTOMER
2. THE RETENTION LATCH OF THE RETAINER MUST BE OUT SIDE OF PLUG HOUSING WHEN PRE-ASSEMBLY
3. RETAINER RETENTION FORCE FROM HOUSING : 20N MIN
4. INSTRUCTION SHEET NO : 411-5928
5. PART NUMBER OF CAP HOUSING TO BE MATED : SEE TABLE - 1
6. APPLIED TERMINAL : SEE TABLE - 2

1. プラグハウジングにリテーナーを仮止して出荷する
2. 仮止時リテーナー突起がハウジングの外側に出ていること
3. リテーナーの仮止保持力は 20N 以上
4. 取扱い説明書 NO : 411-5928
5. 嵌合相手型番は TABLE - 1参照
6. 適用端子は TABLE - 2参照

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN K. FURUYAMA 01MAY03		
DIMENSIONS: mm		CHK S. HIRANUMA 01MAY03		
TOLERANCES UNLESS OTHERWISE SPECIFIED: 一般公差 = ± 0.3		APVD K. ASAI 01MAY03	NAME 025 SERIES 28POSITION PLUG HOUSING ASSEMBLY	
		PRODUCT SPEC 108-5668	RESTRICTED TO	
MATERIAL PBT		FINISH SEE TABLE - 3	APPLICATION SPEC 114-5250	SIZE A3
		WEIGHT 4.13g	CAGE CODE 00779	DRAWING NO 1565380
		CUSTOMER DRAWING	SCALE 2:1	SHEET 1 OF 1

1470-19 (3/11)