

APPLICABLE STANDARD		ANSI/TIA/EIA-568-B.2.10 CAT6a				
RATING	OPERATING TEMPERATURE RANGE	① -25 °C TO 60 °C	STORAGE TEMPERATURE RANGE	-25 °C TO 60 °C		
	VOLTAGE	125 V AC	OPERATING HUMIDITY RANGE	95 % MAX		
	CURRENT	1 A	APPLICABLE CABLE	—		
SPECIFICATIONS						
ITEM		TEST METHOD		REQUIREMENTS	QT	AT
CONSTRUCTION						
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.	X	X
MARKING		CONFIRMED VISUALLY.			X	X
<p>① THE OPERATION TEMPERATURE INCLUDES THE TEMPERATURE RISE BY CURRENT CARRYING. ② TEMPERATURE RANGE FOR A CONNECTOR UNMATED. ③ USE UNDER THE CONDITION RECOMMENDED BY A CABLE MANUFACTURE.</p>						
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	
△						
REMARK				APPROVED	YH. ENAMI	09.06.02
				CHECKED	YH. ENAMI	09.06.02
				DESIGNED	MT. ITANO	09.06.02
Unless otherwise specified, refer to JIS C 5402.				DRAWN	MT. ITANO	09.06.02
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELG4-126868-02	
HRS	SPECIFICATION SHEET		PART NO.	TM31P-TM-88P (02)		
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL222-4626-7-02	△	1/1