


Note:


- Material: Housing-polycarbonate, clear Terminal-0.36[.014] thick phosphor bronze. Thick gold in localized gold plate. Area, Gold Flash over the remainder. Over 2.54mm[.000100] thick nickel underplate.

SEC:△=△

P1	P2
2 BLACK	5
3 RED	4
4 GREEN	3
5 YELLOW	2



Part Number	Drawing Number	Wire Length "L"	Jacket Color	Cut Length
AT-S-26-6/4/B-5	A	1,525±20(5ft)	Black	1,525-1,535mm
AT-S-26-6/4/B-7	B	2,135±30(7ft)	Black	2,135-2,145mm
AT-S-26-6/4/B-10	C	3,050±60(10ft)	Black	3,050-3,060mm
AT-S-26-6/4/B-12	D	3,660±60(12ft)	Black	3,660-3,670mm
AT-S-26-6/4/B-14	E	4,270±60(14ft)	Black	4,270-4,280mm
AT-S-26-6/4/B-25	F	7,625±100(25ft)	Black	7,625-7,635mm
AT-S-26-6/4/B-50	G	15,250±150(50ft)	Black	15,250-15,260mm

Scale	Free				Date	Name	Title	
TOLERANCE					Drawn	08.07.13	Wilson	Modular cable - Straight
X.	±X				Approved	08.07.13	Groll	6P4C 50µ", 26AWG, Black, 5-50 feet
X.X	±X							ASSMANN WSW-No.
X.XX	±X							AT-S-26-6/4/B-xx
DIM	TOL							Drawing-No.
X.°	±X°							rev00
X.X°	±X°							Sheet
Angle	TOL	Id.	Modification	Date	Name			1/1
						<small>1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283 Toll Free: 1-877-277-6266 • Email: info@assmann.us</small>		

Unit: mm

