



- NOTES :
- ▲ MATERIALS AND FINISH:  
 - HOUSING: PA66  
 - CONTACTS: BRASS, FINISH: TIN OVER NICKEL UNDERPLATE
- MUST COMPLY WITH DIRECTIVE 2002/95/EC (ROHS)
  - WIRE TYPES AND SIZES ACCEPTED  
 WIRE RANGE: 20AWG~28AWG.  
 STRIP LENGTH: 5.5mm~6.5mm
  - PACKAGED IN TRAY.
  - CURRENT RATING: 4Amp AC150V.
  - OPERATION TEMPERATURE: -40°C TO +105°C
  - THIS PART NO. IS THE SAME STRUCTURE AS THE SERIES: 2834084
  - THE DATASHEET AND MORE DETAILS PLEASE FOLLOW THE SERIES: 2834084

REV	DATE	BY	CHK	APV
1	08DEC2015			

NO. OF POSN	PART NO	DESCRIPTION	DATE	BY	CHK	APV
2 POSN	2834084-1	WIRE PROTECTOR				
3 POSN	2834084-2	CONTACT				
4 POSN	2834084-3	COVER				
5 POSN	2834084-4	HOUSING				
6 POSN	2834084-5					
7 POSN	2834084-6					
8 POSN	2834084-7					

THIS DRAWING IS A CONTROLLED DOCUMENT.

STI TE Connectivity

NAME: 2.5 45Entry Screwless Connector

DATE: 08DEC2015

REV: A

SIZE: A2

SCALE: 1:1

SHEET: 1 OF 1

REV: A