

NON-ISOLATED DC/DC CONVERTERS

3.3 Vdc Input 0.9 Vdc - 2.5 Vdc/7 A Output

bel
POWER PRODUCTS

xRAH-07C1A0 RoHS Compliant Rev.A

- Non-Isolated
- Fixed Frequency
- High Efficiency
- High Power Density
- UL60950-1 Recognized (UL/cUL)
- Remote On/Off
- Input Under Voltage Lockout
- OCP/SCP
- Wide Range Trim
- Low Cost



Description

The Bel xRAH-07C1A0 module is a series of non-isolated, step down dc/dc power converters that operate from a nominal 3.3 Vdc source. These converters are available in a range of output voltages from 0.9 Vdc to 2.5 Vdc (default output voltage is 1.8 Vdc). It is packaged in a compact, overmolder package rated at 7 A. Optional lead forming provides a vertical mount product for minimal footprint or a surface mount option for a very low profile. The output is closely regulated and the efficiency is typically 92% at full load.

Part Selection

Output Voltage	Input Voltage	Max. Output Current	Max. Output Power	Typical Efficiency	Part Number Surface Mount	Part Number Vertical Mount
0.9 Vdc - 2.5 Vdc	3.3 Vdc	7 A	17.5 W	92%	SRAH-07C1A0	VRAH-07C1A0

- Notes:** 1. Add "0" suffix at the end of the model number to indicate "Tube Packaging", and "R" for "Reel Packaging", and "G" for "Tray Packaging".
2. All part numbers above indicate RoHS 6. Change the second letter "R" to "7" for RoHS 5 part numbers.

Absolute Maximum Ratings

Parameter	Min	Typ	Max	Notes
Input Voltage (continuous)	-0.3 V	-	6 V	
Output Enable Terminal Voltage	-0.3 V	-	6 V	
Ambient Temperature	-40 °C	-	85 °C	
Storage Temperature	-40 °C	-	125 °C	

Input Specifications

Parameter	Min	Typ	Max	Notes
Input Voltage	3 V	-	3.6 V	
Input Current (no load)	-	-	110 mA	
Input Current (full load)				
Vo=2.5 V	-	-	6.6 A	
Vo=1.8 V	-	-	5.3 A	
Vo=1.5 V	-	-	4.6 A	
Vo=1.2 V	-	-	3.8 A	
Vo=1.0 V	-	-	3.2 A	
Vo=0.9 V	-	-	3.0 A	
Remote Off Input Current	-	7 mA	15 mA	
Input Reflected Ripple Current (pk-pk)	-	150 mA	250 mA	With simulated source impedance of 500 nH, 5 Hz to 20 MHz and a 270 uF/16 V with ESR=0.03 ohm max. at 100 kHz
Input Reflected Ripple Current (rms)	-	50 mA	80 mA	
I ² t Inrush Current Transient	-	0.08 A ² s	0.16 A ² s	
Turn on Voltage Threshold	2.5 V	-	2.8 V	
Turn off Voltage Threshold	-	2.4 V	-	

NON-ISOLATED DC/DC CONVERTERS

3.3 Vdc Input 0.9 Vdc - 2.5 Vdc/7 A Output



Output Specifications

Parameter		Min	Typ	Max	Notes		
Output Voltage Set Point	Vo=2.5 V	2.450 V	2.5 V	2.550 V	Test conditions: Vin=3.3 V, Io= full load		
	Vo=1.8 V	1.764 V	1.8 V	1.836 V			
	Vo=1.5 V	1.470 V	1.5 V	1.530 V			
	Vo=1.2 V	1.176 V	1.2 V	1.224 V			
	Vo=1.0 V	0.980 V	1.0 V	1.020 V			
	Vo=0.9 V	0.882 V	0.9 V	0.918 V			
Line Regulation	Vo=1.5 V-2.5 V	-	±3 mV	±10 mV			
	Vo=0.9 V-1.2 V	-	±1 mV	±5 mV			
Load Regulation	Vo=1.5 V-2.5 V	-	±3 mV	±10 mV			
	Vo=0.9 V-1.2 V	-	±1 mV	±5 mV			
Regulation Over Temperature (-40 °C to +85 °C)	Vo=2.5 V	-	±25 mV	±40 mV			
	Vo=1.8 V	-	±15 mV	±30 mV			
	Vo=1.5 V	-	±15 mV	±30 mV			
	Vo=1.2 V	-	±10 mV	±20 mV			
	Vo=1.0 V	-	±8 mV	±15 mV			
	Vo=0.9 V	-	±8 mV	±15 mV			
Output Current		0 A	-	7 A			
Current Limit Threshold		8.4 A	-	17.5 A			
Short Circuit Surge Transient		-	0.08 A ² s	0.12 A ² s			
Ripple and Noise (rms)	Vo=2.5 V-0.9 V	-	10 mV	20 mV	Test condition: 0-20 MHz BW, with a 1 uF ceramic capacitor and 10 uF aluminum capacitor at the output.		
Ripple and Noise (pk-pk)	Vo=2.5 V-1.2 V Vo=1.0 V-0.9 V	- -	40 mV 40 mV	80 mV 70 mV			
Turn on Time		-	7 mS	15 mS			
Overshoot at Turn on		-	0%	1%			
Output Capacitance		0 uF	-	2200 uF			
Transient Response							
50% ~ 100% Max Load	Overshoot	Vo=1.8 V- 2.5 V	-	120 mV	180 mV	Test conditions: di/dt = 0.5 A/uS; Vin = 3.3 V; without any external capacitor at the output.	
	Settling Time		-	40 uS	80 uS		
100% ~ 50% Max Load	Overshoot		-	120 mV	180 mV		
	Settling Time		-	40 uS	80 uS		
50% ~ 100% Max Load	Overshoot		Vo=1.5 V	-	100 mV		150 mV
	Settling Time			-	40 uS		80 uS
100% ~ 50% Max Load	Overshoot			-	100 mV		150 mV
	Settling Time			-	40 uS		80 uS
50% ~ 100% Max Load	Overshoot	Vo=0.9 V- 1.2 V	-	50 mV	100 mV		
	Settling Time		-	40 uS	80 uS		
100% ~ 50% Max Load	Overshoot		-	50 mV	100 mV		
	Settling Time		-	40 uS	80 uS		

Note: All specifications are typical at nominal input, full load at 25 °C unless otherwise stated.

NON-ISOLATED DC/DC CONVERTERS

3.3 Vdc Input 0.9 Vdc - 2.5 Vdc/7 A Output

bel
POWER PRODUCTS

General Specifications

Parameter	Min	Typ	Max	Notes
Efficiency				Measured at Vin=3.3 V, full load and Ta=25 °C
Vo=2.5 V	90%	92%	-	
Vo=1.8 V	86%	88%	-	
Vo=1.5 V	84%	86%	-	
Vo=1.2 V	81%	83%	-	
Vo=1.0 V	79%	81%	-	
Vo=0.9 V	78%	80%	-	
Switching Frequency	250 kHz	300 kHz	340 kHz	
Output Trim Range	50%	-	146%	Vo=1.8 V
MTBF	3,391,747 hours			Calculated Per Bell Core SR-332 (Vin=3.3 V; Vo=1.8 V; Io = 5.6 A; Ta = 25°C)
Dimensions (surface mount)				
Inches (L x W x H)	0.78 x 0.70 x 0.32			
Millimeters (L x W x H)	19.81 x 17.78 x 8.13			
Dimensions (vertical)				
Inches (L x W x H)	0.70 x 0.308 x 0.65			
Millimeters (L x W x H)	17.78 x 7.82 x 16.51			
Weight	-	5 g	-	

Control Specifications



Parameter	Min	Typ	Max	Notes
Remote On/Off				
Signal Low (Unit Off)	-0.3 V	-	1 V	Remote on/off pin open, unit on.
Signal High (Unit On)	1.8 V	-	3.6 V	

Output Trim Equations

Equations for calculating the trim resistor given the desired adjusted voltage (Vadj) and the nominal output voltage of the converter (Vnom) are shown below. The Trimup resistor should be connected between the Trim pin and Ground and the Trimdown resistor should be connected between the Trim pin and Vout pin.

$$R_{trim_up} = \left(\frac{3.064}{V_{o,adj} - V_o} - 0.261 \right) K\Omega$$

$$R_{trim_down} = \left(\frac{3.8488}{V_o - V_{o,adj}} - 4.091 \right) K\Omega$$









Note: Output voltage Vo=1.8 V when Rtrim is open.

NON-ISOLATED DC/DC CONVERTERS

3.3 Vdc Input 0.9 Vdc - 2.5 Vdc/7 A Output



Efficiency Data




NON-ISOLATED DC/DC CONVERTERS


3.3 Vdc Input 0.9 Vdc - 2.5 Vdc/7 A Output

bel
POWER PRODUCTS

Thermal Derating Curves




VRAH-07C1A0



SRAH-07C1A0

Ripple and Noise Waveforms




Note: Ripple and noise at full load, 3.3 Vdc input, 1.8 Vdc output and $T_a=25$ deg C, with 1 μ F ceramic capacitor and 10 μ F aluminum capacitor at the output.

NON-ISOLATED DC/DC CONVERTERS


3.3 Vdc Input 0.9 Vdc - 2.5 Vdc/7 A Output



Transient Response Waveforms



50% to 100% load Transient at $V_{in}=3.3\text{ V}$, $V_o=1.8\text{ V}$



100% to 50% load Transient at $V_{in}=3.3\text{ V}$, $V_o=1.8\text{ V}$

Note: Transient Response at $di/dt=0.5\text{ A}/\mu\text{S}$, external load capacitance $C_o=0\mu\text{F}$ (electrolytic), $T_a=25\text{ deg C}$.


NON-ISOLATED DC/DC CONVERTERS

3.3 Vdc Input 0.9 Vdc - 2.5 Vdc/7 A Output



Mechanical Outline


SRAH-07C1A0



Pin Connections

Pin	Function
1	Remote On/Off (option)
2	Vin
3	Ground
4	Vout
5	Trim (option)
6	N/A
7	N/A


VRAH-07C1A0



Pin Connections

Pin	Function
1	Remote On/Off (option)
2	Vin
3	Ground
4	Vout
5	Trim (option)

RECOMMENDED PCB PAD LAYOUT



RoHS Compliance

Complies with the European Directive 2002/95/EC, calling for the elimination of lead and other hazardous substances from electronic products. These parts are not however compatible with the higher temperatures associated with lead free solder processes and must be soldered using a reflow profile with a peak temperature of no more than 240 °C.



©2007 Bel Fuse Inc. Specifications subject to change without notice. 010507

CORPORATE

Bel Fuse Inc.
206 Van Vorst Street
Jersey City, NJ 07302
Tel 201-432-0463
Fax 201-432-9542
www.belfuse.com

FAR EAST

Bel Fuse Ltd.
8F/ 8 Luk Hop Street
San Po Kong
Kowloon, Hong Kong
Tel 852-2328-5515
Fax 852-2352-3706
www.belfuse.com

EUROPE

Bel Fuse Europe Ltd.
Preston Technology Management Centre
Marsh Lane, Suite G7, Preston
Lancashire, PR1 8UD, U.K.
Tel 44-1772-556601
Fax 44-1772-888366
www.belfuse.com