




MVK TYPE TERMINALS ARE MANUFACTURED FROM THERMOPLASTIC RAW MATERIAL. GREY BEING THE MAIN COLOR.

MVK SERIES

MINI TERMINAL BLOCKS
FOR USE WITH
15MM WIDE DIN RAIL

MVK 2.5

WIDTH 5 MM
304 429



TORQUE: 1.2 NM

COLORS	TERMINALS	END PLATE
	PART NUMBER	PART NUMBER
	MVK 2.5	NPP
GREY	304 429	444 429
BEIGE	304 420	444 420
	MVK 4	NPP
GREY	304 439	444 429
BEIGE	304 430	444 420



ELECTRICAL RATINGS

TSE / CE (EN 60947-7-1 / EN60947-7-2)

UL

ATEX

CONNECTION DATA

SOLID STRAND, SCREW CON. - FINE STRAND, SCREW CON.

AWG CONDUCTOR / FINE STRAND WITH FERRULE

INSULATION STRIPPING LENGTH / TORQUE

ORDERING DATA

POLYAMIDE 66 GREY
YELLOW-GREEN

END BRACKET

THICKNESS 8MM GREY
KD 5



END PLATE - DISCONNECT PLATE

WIDTH 1.5 MM - GREY
POLYAMIDE 66 YELLOW-GREEN



SMALL PARTITION

POLYAMIDE 66 GREY



CROSS CONNECTION



TEST PLUG-SOC. / INS. TEST SOC.

TF ITK T5K



WARNING LABEL

IP WITH SYMBOL
WITHOUT SYMBOL



GROUP MARKING

GE GREY
GE2



TECHNICAL DATA

- MAX. CLAMPING RANGE / MAX. TECHNICAL DATA
- RATED IMPULSE VOLTAGE / POLLUTION SEVERITY
- INSULATION MATERIAL GROUP / GAUGE PIN CODE ACCORDING TO IEC 60947-1
- PROTECTION CLASS / PROTECTION CONDUCTOR TYPE

MARKING TAGS

SEE PAGES 104 & 105 FOR FURTHER DETAIL

VOLTAGE/CURRENT/CROSS-SECTION

400 V ~ / 24 A / 2.5 MM²

300 V ~ / 20 A / AWG 26-12

400 V ~ / 23 A

0.5 - 4 MM² / 0.5 - 4 MM²

16 - 8 / 0.5 - 2.5 MM²

12 MM / 1.2 NM

TYPE	PART. NO.	QTY.
MVK 2.5	304 429	100

TYPE	PART. NO.	QTY.
KD 5	495 069	100

TYPE	PART. NO.	QTY.
NPP MVK	444 429	100

TYPE	PART. NO.	QTY.
AD1	467 919	100

TYPE	PART. NO.	QTY.
UK 2.5/2	476 222	25

TYPE	PART. NO.	QTY.
UK 2.5/3	476 223	20

TYPE	PART. NO.	QTY.
UK 2.5/4	476 224	15

TYPE	PART. NO.	QTY.
UK 2.5/10	476 229	5

TYPE	PART. NO.	QTY.
TF (Ø2)	493 020	5

TYPE	PART. NO.	QTY.
IP 2 S	498 130	25

TYPE	PART. NO.	QTY.
IP 2	498 140	25

TYPE	PART. NO.	QTY.
GE	496 119	50

TYPE	PART. NO.	QTY.
GE 2	496 250	25

0.2 - 4 MM² / 4 MM² / 32 A

6 kV / 3

I / B3

IP 20 / -