



PACKAGE: INDIVIDUAL PE BAG.

500g Weight

CONDUCTOR: [26AWG (0.12X12) BARE COPPER] X8C
INSULATION: (PP6331 ID: 0.95-1.0) X8C

JACKET: PVC NOUL 80P (flexible material)

- WHITE
- ORANGE
- BLACK
- RED
- GREEN
- YELLOW
- BLUE
- BROWN

NOTE FOR PLUG:
 MATERIAL: HOUSING-POLYCARBONATE, CLEAR.
 TERMINAL-0.36[.014] THICK PHOSPHOR BRONZE.
 THICK GOLD IN LOCALIZED GOLD PLATE.
 AREA, GOLD FLASH OVER THE REMAINDER.
 OVER 2.54mm[.000100] THICK NICKEL
 UNDERPLATE.

| P1 | COLOR |
|----|--------|
| 1 | WHITE |
| 2 | ORANGE |
| 3 | BLACK |
| 4 | RED |
| 5 | GREEN |
| 6 | YELLOW |
| 7 | BLUE |
| 8 | BROWN |

| PART NO | DRAWING NO | BUYER COLOR | VENDOR COLOR | CUSTOMER Accepted ("L2") | Retracted Length ("L3") | CUT LENGTH "L1" |
|----------------------|------------|-------------|--------------|--------------------------|-------------------------|-----------------|
| 523-26-8800-BL-0005F | A | Black | BLACK LIGHT | 5.0FT-5.75FT | 700 ± 50 | 2900-3000 |
| 523-26-8800-BL-0007F | B | Black | BLACK LIGHT | 7.0FT-8.05FT | 1000 ± 50 | 4000-4200 |
| 523-26-8800-BL-0010F | C | Black | BLACK LIGHT | 10.0FT-11.5FT | 1500 ± 50 | 5900-6100 |
| 523-26-8800-BL-0012F | D | Black | BLACK LIGHT | 12.0FT-13.8FT | 1650 ± 50 | 7000-7200 |
| 523-26-8800-BL-0014F | E | Black | BLACK LIGHT | 14.0FT-16.1FT | 1900 ± 50 | 7600-7800 |
| 523-26-8800-BL-0025F | F | Black | BLACK LIGHT | 25.0FT-28.75FT | 3200 ± 50 | 14300-14500 |

| REVISE | VERSION | BASIS | CONTENTS |
|----------|---------|--------|-------------|
| 12-02-20 | A/0 | T0210A | NEW DRAWING |
| | | | |
| | | | |
| | | | |

| | | | |
|---|-----|-----------------|--|
| CnC Tech, LLC Industrial Cable and Connector Technology | | | |
| DRAWING NO: 671-341 | | CUSTOMER: L-671 | |
| ITEM NO: 8C COILD CORD P+O PLUG | | UNIT: mm | |
| DATE: 2012-02-20 | | ISSUE: (A/0) | |
| DRAWN: | QE: | QA: | |
| SALES DEPT: | | SALES MANAGER: | |