



Material

- Ⓐ Terminal body(metal housing of double): Brass(CuZn),Ni plated
- Ⓑ Terminal body(metal housing of single): Brass(CuZn),Ni plated
- Ⓒ Terminal screw: Steel Zinc plating "I" slot type
- Ⓓ Wire guard: Stainless steel
- Ⓔ Insulator (lever): Thermoplastic (UL94V-0)
- Ⓕ Insulator (housing): Thermoplastic (UL94V-0)

Electrical

cULus VDE
 Voltage rating: 400VAC / 450VAC
 Current rating: 10A / 24A
 Wire range: 0.34-2.5mm²
 Solid wire(AWG): 14-22
 Stranded wire(AWG):14-22
 Torque(Lb-In): 3.5 / 0.5
 Screw: M3
 Wire strip length: 7-8mm
 Withstanding Voltage: 1.8KV/2.5KV
 Operating temperature: -40°C to +115°C
 Safety Approval:  

RoHS compliant
 Unit: mm



Scale	Free
TOLERANCE	
X.	±0.50
X.X	±0.30
X.XX	±0.10
DIM	TOL
X.°	±1°
Angle	TOL

Id.	Modification	Date	Name
③	Update to new drawing and add UL	15.03.2016	Amy
②	Updating	19.04.2010	Alex
①	Drawn	16.06.2006	Hellwig

ASSMANN
 WSW components

Customer-No.	Drawing-No.	Replace
ASSMANN WSW-No.	A-TB100-TM03	ASS 2011C CO
		rev03

1	2	3	4	5	6	7
A	B	C	D	E	F	G
H	H	H	H	H	H	H